






Beadboard Single Shelf

Note: The hanging hardware included with this shelf is meant for drywall and wood stud mounting only. If your walls are made from concrete, brick or plaster (or other), please consult your local hardware store for assistance in selecting the appropriate hardware. For safety and ease of mounting, installation is recommended using two people.

Load limit is 75 lbs.

Parts Included:

A 	B 	C 
Wall-mount Cleat 1PCS	Toggles 3PCS	Screws 3PCS

Tools required for mounting (not included): Phillips screwdriver, Level, Pencil, Tape measure

This item uses a French cleat system for hanging to a wall at a desired mounting location. The cleat system employs two separate cleats, a wall mount cleat which is mounted to the wall using the provided hardware, and a product-mounted cleat which is already mounted to the back of the shelf. The wall-mounted cleat should come pre-attached to the product mounted cleat using tape. Keep the cleats secured to each other at this time.

Mounting Instructions:

1. With the help of one or two other people, hold the shelf against the wall and at a desired mounting location. Use a level to ensure that the product is level and then use a pencil to gently mark the wall along the top edge of the shelf. Set the shelf aside.
2. As mentioned above, the cleat should be taped to the back of the shelf. If it has separated, use tape to re-secure it with its sharp edge nested up into the recess located on the back of the shelf.
3. Using a tape measure, measure the distance from the top edge of the shelf to the bottom edge of the attached wall-mounted cleat. This will be "measurement (A)". Use the pencil and the tape measure to make a lower line below the line you drew in Step (1). The lower line will be spaced a distance equal to "measurement (A)".
4. Separate the wall-mounted cleat from the shelf and position its bottom edge (opposite the sharp edge) along the lower line. The sharp edge should be facing up and should be away from the wall surface. With the help of another person, hold the cleat against the wall along the lower line and use a pencil or a thin sharp object (such as one of the provided screws) to mark the wall through each of the three holes located in the cleat. These three marks will be the insertion points for the hardware.
5. Use a Phillips screwdriver to engage a provided toggle and position the sharp tip of the toggle against the wall at one of the three marks (insertion points). Firmly push the toggle into the wall as you rotate it clockwise. The toggle is designed to drive itself into the wall as it is rotated. Continue rotating the toggle

until its wide end becomes even with the wall surface. Repeat this step with the other toggles and other marks.

6. Again, with the help of another person, hold the cleat against the wall so that the three holes therein align with the installed toggles (make sure that the sharp edge is facing up and is away from the wall). Insert a screw into each hole and into each toggle. Use the screwdriver to tighten each screw.

Note: If either mark aligns with a wall-stud, use only the screw at that mark. Do not use the toggle.

Hanging the product:

- a) Carefully position the product so that the wall mounted cleat nests within the recess located on the back of the shelf.
- b) Lower the product until the cleat engages with the back of the shelf. Gently tap the top of the shelf to ensure complete cleat-engagement.
- c) Your product is ready for use.

Care Instructions:

- Wipe with a soft, dry cloth
- Do not use glass cleaner, abrasives, wax or household cleaners as they may damage the finish on the product

