


QUINCY DESK HUTCH

ASSEMBLY INSTRUCTIONS



Important Safety Instructions:

- Please read all instructions carefully before assembling this desk.
- For your safety, assembly by two or more adults is strongly recommended.
- Keep these instructions for future use.
- Use only vendor-supplied hardware to assemble this item. Using unauthorized hardware could jeopardize the structural integrity of the item.

Pre-assembly:

- Remove all parts and hardware from the box. Place them on a carpeted or scratch-free work surface, as this will
 avoid damaging parts during assembly. The shipping box provides an ideal work surface.
- To avoid accidentally discarding small parts or hardware, do not dispose of any packaging or contents of the shipping carton until assembly is complete.
- Use the parts and hardware lists below to identify, and separate each of the pieces included.
- The illustrations provided allow for easier assembly when used in conjunction with the assembly instructions.
- The use of power tools to aid in assembly is not recommended. Power tools can damage hardware and split wood.

Date: 2013-Apr-10 www.pbteen.com Page 1 of 2

Rev:

Parts Included:

(A) Hutch (1x)

Hardware Included:





(B) Mending Plate – 2x

(C) Machine Screw 13mm - 4x

Tools Required:


Philips Head Screw Driver



(not included)

Assembly Instruction Steps:

- 1. When connecting the hutch to a Quincy Desk (sold separately), simply place the Hutch on top of the desktop.
- 2. Place the Mending Plates (B) over the metal inserts on the backside of the desk and hutch.
- 3. Secure with Machine Screws (C) using a Philips Head Screwdriver, as seen in the illustration below.



Care Instructions:

- Dust often using a clean, soft, dry, and lint-free cloth.
- Blot spills immediately and wipe with a clean, damp cloth.
- We do not recommend the use of chemical cleansers, abrasives, or furniture polish on our lacquered finish.
- Hardware may loosen over time. Periodically check to make sure all connections are tight.
 Re-tighten if necessary.

Rev: